

ViewSonic® PROJECTOR PX701HD

Key Features

- Energy-efficient SmartEco+ Mode
- Vertical Lens Shift
- vColorTuner
- Customised User Modes
- Dual HDMI inputs and USB power supply




Product Description

The ViewSonic PX701HD is a high brightness 3,500 ANSI lumens projector featuring a Full HD 1080p resolution that offers impressive visual performance in a brightly lit living room or meeting room. The projector adopts the latest lamp design to extend lamp life up to 20,000 hours under SuperEco+ mode, effectively reducing lamp replacement and maintenance costs. A digital lens shift allows users to make adjustments by remote control, and it's also compatible with the vColorTuner function for colour profile exchange and adjustments. The dual HDMI inputs and USB power supply allow users to connect to a multitude of multimedia devices for gaming, movies, or a wireless dongle for wireless presentation.



1. Keypad
2. LED indicator
3. Power Key
4. Zoom/Focus
5. Front IR
6. Projection Lens
7. Audio in/out



8. Dual HDMI
9. USB Type A
10. Computer in
11. Monitor out
12. RS232
13. Kensington® Lock Slot

Visit Us  www.viewsonic.com

CONTROL

RS232 (DB 9-pin male):	1
------------------------	---

SPECIFICATION

Native Resolution:	1920x1080
--------------------	-----------

DMD Type:	DC3
-----------	-----

Brightness:	3500 ANSI Lumens
-------------	------------------

Contrast Ratio with SuperEco Mode:	22,000:1
------------------------------------	----------

Display Colour:	1.07 Billion Colours
-----------------	----------------------

Light Source Type:	Lamp
--------------------	------

Light Source Life (Normal):	5000
-----------------------------	------

Light Source Life (SuperEco):	20000
-------------------------------	-------

Lamp Watt:	203W
------------	------

Lens:	F=2.0~2.05,f=15.843mm~17.445mm
-------	--------------------------------

Projection Offset:	110%+/-6%
--------------------	-----------

Throw Ratio:	1.5-1.65
--------------	----------

Image Size:	30" - 300"
-------------	------------

Throw Distance:	1m~10.96m (100"@3.32m)
-----------------	------------------------

Keystone:	+/- 40° (V)
-----------	-------------

Lens Shift V. Range:	Yes (+/- 5%)
----------------------	--------------

Optical Zoom:	1.1x
---------------	------

Digital Zoom:	0.8x ~ 2.0x
---------------	-------------

Audible Noise (Normal):	31dB
-------------------------	------

Audible Noise (Eco):	27dB
----------------------	------

Input Lag:	16ms
------------	------

Resolution Support:	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB-Reduced Blanking
---------------------	---

HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
---------------------	--

Video Compatibility:	NTSC, PAL, SECAM
----------------------	------------------

Horizontal Frequency:	15K~102KHz
-----------------------	------------

Vertical Scan Rate:	23~120Hz
---------------------	----------

INPUT

Computer in (share with component):	1
-------------------------------------	---

Audio-in (3.5mm):	1
-------------------	---

HDMI:	2 (HDMI 1.4/ HDCP 1.4)
-------	---------------------------

OUTPUT

Monitor out:	1
--------------	---

Audio out (3.5mm):	1
--------------------	---

Speaker:	10W
----------	-----

USB Type A (Power):	1 (5V/1.5A)
---------------------	-------------

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
-----------------------	--------------------------------

Power Consumption:	Normal: 300W Standby: <0.5W
--------------------	--------------------------------

Operating Temperature:	0~35°C
------------------------	--------

Net Weight:	2.59kg
-------------	--------

Dimensions (WxDxH) with Adjustment Foot:	312x222x108mm
--	---------------

OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese
---------------	---

STANDARD ACCESSORY

Power Cord:	1
-------------	---

VGA Cable:	1
------------	---

Remote Control:	1
-----------------	---

QSG:	1
------	---

OPTIONAL ACCESSORY

Lamp/Light Source:	RLC-119
--------------------	---------