

4K   **android**
Quad-core 400nits

AZTECH DIGITAL SIGNAGE

AZ-FDS-55 | AZ-FDS-55T





SPECIFICATION

Memory

Panel Size (Inches)	55
Panel Type	DLED
Resolution	2160 x 3840
Pixel Pitch (H x V) (mm)	0.63 x 0.63
Contrast Ratio	1200:1
Brightness (cd/m ²)	400
Color Support	16.7M
Refresh Rate	60Hz
Response Time (ms)	8
Viewing Angle (H/V)	178°/178°
Display Size (H x V) (mm)	680.4 (H) x 1209.6 (V)

System

CPU structure	RK3568
Number of cores	4 x A55
CPU working frequency	Maximum main frequency 2.0GHz
GPU	4 x G52
RAM	4GB
ROM	64GB
System version	Android 11

Interface

Interface	1X LAN (100m) , 1x AUDIO IN , 1x USB OTG (TYPE-C USB2.0), 1x USB 2.0 HOST, 1x USB 3.0 HOST (TYPE-A), 1x AC
-----------	--

SPEAKER

Speaker	5W x 2
---------	--------

OSD

Languages	English
-----------	---------

TOUCH PARAMETERS (AZ-FDS-55T)

Glass	3mm Tempered Glass
Touch Technology	Infrared
Touch Points	20 Points



www.aztechmea.com

AZTECH INNOVATION TECHNOLOGIES LLC

SPECIFICATION

General

Input Voltage	AC 100V~240V, 60-50HZ
Typical power consumption (W)	≤55
Standby power consumption (w)	<0.5
Product Dimensions (W x H x D) (MM)	AZ-FDS-55 - 1800(H) × 746(V) × 95(D) AZ-FDS-55T - 1810.7(H) × 756.7(V) × 51.8(D)
Product Dimensions (W x H x D) (MM)	AZ-FDS-55 - 1900(H) × 190(D) × 860(V) AZ-FDS-55T - 1940(H) × 845(V) × 180(D)
Weight (Kg)	AZ-FDS-55 - Net Weight: 46Kg, Gross Weight: 52.5Kg AZ-FDS-55T - Net Weight: 52.5Kg, Gross Weight: 58.4Kg
Operation Temperature	0°C ~ 40°C
Operating Humidity	20% ~ 85% RH without condensation
Storage Temperature	-10°C ~ 60°C
Storage Humidity	10% ~ 90% RH without condensation
Standard	1x Remote control, 1x Power supply, 1x WiFi antenna, 1x Quick start, 1x Stand up base, 1x Key
Attention	The above parameters may differ from specific products. Please refer to the actual product or consult local sales personnel

DIMENSIONS

