

WorkForce Pro

WF-C878RDTWFC (MEA)



Cut your downtime, save cost and improve sustainability with this ultra-reliable business inkjet MFP

Reduce energy use and downtime, while still maintaining high productivity with Epson's WorkForce Pro RIPS WF-C878R. Thanks to this ultra-reliable business inkjet multifunction printer, users can print up to 20,000 pages without needing to change supplies.¹

High yield printing

This low-intervention MFP prints up to 20,000 pages in mono or colour without changing the ink supplies.¹ This means there is low user intervention, increasing productivity.

Precision Core Heat-free technology

Epson Heat-Free Technology requires no heat to warm up when it is switched on or woken from sleep, which significantly reduces energy consumption and therefore saves money. This also means Epson's Heat-Free inkjets can deliver a fast first page out time (FPOT) of 5.5 seconds compared to laser printers, which need to preheat the fuser to print.

Enhance functionality with in-house (EDA, EPA) and third party solutions (Open Platform)

Gain complete control of printing operations with Epson and its partners solutions, allowing devices to be set up to meet specific and changing business requirements.

Epson Remote Services (ERS)

Our cloud-based device monitoring and management system helps service providers to perform accurate remote diagnosis without compromising on security. The embedded agent on the WF-C878R allows for seamless setup and use.

DATASHEET



KEY FEATURES

- **High reliability**
With few moving parts, and low intervention, increase printer uptime
- **High print yield**
Print up to 20,000 pages without changing the supplies¹
- **Low power consumption**
Epson's Heat-Free technology uses no heat, reducing energy consumption
- **Epson Remote Services**
Cloud-based, advanced diagnosis of Epson printers and MFPs.

PRODUCT SPECIFICATIONS

TECHNOLOGY

Printing Method	PrecisionCore™ Print Head
Nozzle Configuration	800 Nozzles Black, 800 Nozzles per Color
Minimum Droplet Size	4.6 pl, With Variable-Sized Droplet Technology
Ink Technology	Replaceable Ink Pack System (RIPS)
Category	Office Workgroup, Office Departmental
All-in-One Functions	Print, Scan, Copy, Fax

PRINT

First Page Out	Monochrome 5.5 Seconds, Colour 5.5 Seconds
Printing Speed ISO/IEC 24734	25 pages/min Monochrome, 24 pages/min Colour
Duplex Printing Speed ISO/IEC 24734	17 A4 Pages/min Monochrome, 16 A4 Pages/min Colour
Maximum Printing Speed	35 pages/min Colour (plain paper 75 g/m ²), 35 pages/min Monochrome (plain paper 75 g/m ²)
Printing Resolution	4,800 x 1,200 DPI
Printing Volume	75,000 pages per month

The maximum number of printed pages per month based on the performance capabilities of the printer, including ISO rated print speeds and paper handling capabilities.

Colours Black, Cyan, Yellow, Magenta

For detailed information on printing speeds please visit <http://www.epson.eu/testing>.

SCAN

Double-sided scanning	Yes
Single-sided scan speed (A4 black)	25 ipm with ADF scan 200 dpi (flatbed) 4 sec. with flatbed scan
Doubled-sided scan speed (A4 black)	200 dpi (with ADF); , 45 ipm with ADF scan
Single-sided scan speed (A4 colour)	200 dpi (with ADF); , 25 ipm with ADF scan 200 dpi (flatbed) 4 sec. with flatbed scan
Doubled-sided scan speed (A4 colour)	200 dpi (with ADF); , 45 ipm with ADF scan
Optical Resolution	600 DPI x 600 DPI (Horizontal x Vertical)
Optical Resolution (ADF)	600 DPI x 600 DPI (Horizontal x Vertical)
Output formats	JPEG, TIFF, PDF
Scanner type	Contact image sensor (CIS)

FAX

Type of fax	Walk-up black and white and colour fax capability
Fax Transmission Speed	Up to 33.6kbps / Approx. 3 sec/page
Error correction mode	CCITT/ITU Group3 fax with Error Correction Mode
Fax speed dials (max)	2,000 names and numbers
Page memory	Up to 550 pages/ 6MB (ITU-T No. 1 chart)
Fax Functions	PC Fax, Fax to E-mail, Memory Reception, Auto Redial, Speed Dial, Fax to Folder, Address Book

CONNECTIVITY

Network Protocol	IPv4, IPv6
Interfaces	Hi-Speed USB - compatible with USB 2.0 specification, Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base-T), USB host, Wi-Fi Direct, USB 2.0-A (2x), Wireless LAN IEEE 802.11a/b/g/n, USB 3.0 Type B
WLAN Security	WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA2 PSK (AES), WPA2 Enterprise (AES)

WorkForce Pro WF-C878RDTWFC (MEA)

WHAT'S IN THE BOX

- Quick Setup Guide
- Main unit
- Warranty Documents
- User manual (CD)
- Power cable
- Paper tray
- Initialization Ink Supply Units

PRODUCT SPECIFICATIONS

WorkForce Pro WF-C878RDTWFC (MEA)

PAPER / MEDIA HANDLING

Paper Formats	A4 (21.0x29.7 cm), A5 (14.8x21.0 cm), A6 (10.5x14.8 cm), B5, C4 (Envelope), C6 (Envelope), No. 10 (Envelope), Letter, 10 x 15 cm, 13 x 18 cm, 20 x 25 cm, Legal, A3 (29.7x42.0 cm), B4, B6, C5 (Envelope), DL (Envelope), HLT, EXE, Tabloid, A3+
Automatic Document Feed	50 pages
Compatible Paper Weight	64 g/m ² - 300 g/m ²
Duplex	Yes
Output Tray Capacity	250 Sheets
Paper Tray Capacity	835 Sheets Standard, 1,835 Sheets Maximum
Rear paper path (special media)	Yes
Number of paper trays	4

PAPER FEED RASF

Paper Input Name	RASF
Paper Formats	A3+, A3, A4, C4 (Envelope), Letter, User defined, Legal
Compatible paper weight	64 g/m ² - 300 g/m ²
Paper Capacity 1	Sheets of Plain Paper, 80gsm

PAPER FEED C1

Paper Input Name	C1
Paper Formats	A3+, A4, Letter, User defined
Compatible paper weight	64 g/m ² - 200 g/m ²
Paper Capacity 1	250 Sheets of Plain Paper, 80gsm

PAPER FEED C2

Paper Input Name	C2
Paper Formats	A3, A4, Letter, User defined
Compatible paper weight	64 g/m ² - 200 g/m ²
Paper Capacity 1	Sheets of Plain Paper, 80gsm

GENERAL

Energy Use	40 Watt (standalone copying, ISO/IEC 24712 pattern), TEC 0.22 kWh/week
Supply Voltage	AC 220 V - 240 V
Product dimensions	621 x 652 x 1,107 mm (Width x Depth x Height)
Compatible Operating Systems	Citrix XenApp 7.x, Linux, Mac OS 10.10.x, Mac OS 10.11, Mac OS 10.6+, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Microsoft Windows XP (Home Edition / Prof / Prof X64 / Vista), SAP, Windows 10, Windows 7, Windows 7 x64, Windows 8 (32/64 bit), Windows 8.1, Windows 8.1 x64 Edition, Windows Server 2003 (32/64bit), Windows Server 2008 (32/64bit), Windows Server 2008 R2, Windows Server 2012 (64bit), Windows Server 2012 R2, Windows Server 2016, Windows Vista, Windows Vista (32/64 bit), Windows Vista x64, Windows XP x64, Windows Server 2003 R2
Sound Power	Operation: 6.6 B (A)
Noise	Operation: 51 dB (A)
Mobile and Cloud printing services	Epson Connect (iPrint, Email Print, Remote Print Driver, Scan-to-Cloud), Apple AirPrint, Google Cloud Print
Power supply	100V, 110V, 220V, 240V

ADDITIONAL FEATURES

Features	Touchscreen, Direct scan-to-print without PC, Direct print from USB
Panel	Type: Color, Touchscreen, Diagonal: 12.7 cm
Media Handling	Automatic duplex (A4/A3, plain paper), Portrait & Landscape printing, Rear specialty media feed, Thick Media Support

OTHER FEATURES

Emulations	PCL6, PCL5c, PCL5e, ESC/P-R, PDF 1.7, PostScript 3
------------	--

OTHER

Warranty	12 months On-site service Optional warranty extension available
----------	--

SUPPLIES

● DURABrite Pro	C13T05A100	20,000 pages
● DURABrite Pro	C13T05A200	20,000 pages
● DURABrite Pro	C13T05A300	20,000 pages
● DURABrite Pro	C13T05A400	20,000 pages
● Maintenance box	C13T671400	
● Standard Cassette Maintenance Roller	C13S210048	200,000 pages
● Optional Cassette Maintenance Roller	C13S210049	200,000 pages

OPTIONAL ACCESSORIES

- Card Reader Holder
C12C932921

LOGISTICS INFORMATION

SKU	C11CH60402BS
EAN code	8715946675558
Country of Origin	Indonesia

WorkForce Pro WF-C878RDTWFC (MEA)



Epson Middle East
P.O.Box 17383, Dubai
United Arab Emirates
Telephone: +9714 8818934

Hotline Telephone: +9714 8872172
Fax: +9714 8818945
www.epson.ae

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

1. 1Approx. page yield with the WF-C878R. Actual yield will vary depending on images printed and usage conditions. For more information visit www.epson.eu/pageyield.

EPSON[®]