



SLOT IN PCS

VPC27-S53-O1-1B

Key Features

- Ideal Integrated Solution for ViewBoard® Interactive Displays & Commercial Displays
- Powerful Intel® 10th Core Processors
- Improved System Stability, Security, & Thermal Control



Product Description

Seize the power to get more done when you sync your ViewBoard® interactive displays and wireless presentation display with the ViewSonic VPC27-S53-O1-1B slot-in PC. Integrated with exceptional performance from Intel® 10th Gen Core™ processors, 16GB DDR4 memory, and up to 256GB of SSD storage, experience enhances computing performance to breeze through complex classes and collaborations. Plug into pure productivity with dual-band WiFi, Bluetooth 5.2, and a range of ports, including 4K HDMI, DP1.2, USB 3.2, and Gigabit LAN RJ45 for faster workflows.



- 01. HDD/Power LED
- 02. MIC-IN
- 03. LINE-OUT
- 04. Power Button

- 05. HDMI
- 06. Type C
- 07. DP
- 08. USB 3.2

- 09. Reset
- 10. LAN

- 1. HDD/Power LED
- 2. LINE-OUT
- 3. MIC-IN
- 4. Power Button
- 5. HDMI
- 6. Type C
- 7. DP
- 8. USB 2.0
- 9. Reset
- 10. USB 3.2
- 11. LAN

Visit Us www.viewsonic.com

CORE

CPU:	Intel Core i7-10700T 2.0GHz Turbo boost 4.5GHz, (TPM 2.0 support)
Graphics:	Integrated Intel® UHD graphic 630 Intel H510 chipset

MEMORY

Capacity:	16GB DDR4
-----------	-----------

SOFTWARE

Operating System:	UEFI Shell
-------------------	------------

STORAGE

Dimension:	M.2 2280 (22 x 80 mm)
------------	-----------------------

Capacity:	256GB SSD
-----------	-----------

Interface:	M.2 2280 NVMe PCIe Gen3 SSD
------------	--------------------------------

INPUT

MIC(Microphone):	x1
------------------	----

OUTPUT

DisplayPort:	x 1 (1.2, resolution 3840x2160@60Hz)
--------------	---

HDMI:	x 1 (1.4, resolution 3840x2160@60Hz)
-------	---

Audio:	x 1 Line out
--------	--------------

LAN

RJ45:	GbE LAN Port
-------	--------------

WIRELESS / BLUETOOTH

Intel AX200 WiFi 6 + BT5.2 Module dual band

USB

Type A:	USB x 4 (USB 3.2 x 1, USB 2.0 x 3)
---------	---------------------------------------

Type C:	x 1 (data only)
---------	-----------------

POWER

Voltage:	DC in +12V~+19V @ 3.42A
----------	----------------------------

Consumption:	65 W (Typical)
--------------	----------------

OPERATING CONDITIONS

Temperature (° C):	-5~45°C
--------------------	---------

Humidity:	20% ~ 80% R.H. Non- Condensing
-----------	-----------------------------------

DIMENSIONS (W X H X D)

Physical (inch / mm):	7.95" x 4.69" x 1.18" / 202 x 119 x 30 mm
-----------------------	--

Packaging (inch / mm):	10.00" x 7.72" x 3.03"/254 x 196 x 77 mm
------------------------	---

WEIGHT

Net (lb / kg):	2.205 lb/1 kg
----------------	---------------

Gross (lb / kg):	2.646 lb/1.2 kg
------------------	-----------------

REGULATIONS

cTUVus, FCC-B w/ ICES003, FCC ID+SDOC, CA IC, IC VOC, NOM, COFETEL, CE EMC, CE RED, CE LVD, CB, RoHS, REACH, WEEE, BSMI, NCC, BIS, WPC, RCM, MIC, VCCI, VNTA, CCC, SRRC
--

PACKAGE CONTENTS

1. VPC OPS
2. Quick Start Guide
3. Screw x 2